

GE Sensing

Features

- Measure and simulate RTDs
- Automatic detection of two-, three- and four-wire RTDs highlights faulty probes
- mA measure, switch test and 24V loop power
- Large backlit display, menu driven interface
- HART® loop resistor
- Robust and weatherproof
- Compact, simple to use, easy to carry
- Convenient, one-handed operation
- Secure grip, impact resistant, elastomer protection
- Plug and play connector for Intelligent Digital Output Sensor (IDOS™) Universal Measurement Modules

Applications

- Temperature test and maintenance
- Transmitter calibration
- Loop set-up and diagnostics
- Switch testing

The DPI 800 Series is a complete range of advanced, robust and simple to use hand-held instruments. Highly cost effective, these tools are ideal for test/calibration of many popular process parameters. Advanced features and technical innovations address more applications in less time and deliver results you can rely on.

DPI 811/812

Druck RTD Calibrator/ Loop Calibrator

DPI 811/812 is a Druck product. Druck has joined other GE high-technology sensing businesses under a new name—GE Sensing.






DPI 811/812 Specifications

| | DPI 800 | DPI 802 | DPI 811 | DPI 812 | DPI 820 | DPI 821 | DPI 822 | DPI 832 | DPI 841 | DPI 842 |
|---|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Type | P | P | RTD | °F (°C) | TC | mA/V | Hz | | | |
| Indicator (measure pressure) | ✓ | ✓ | | | | | | | | |
| Calibrator (measure or source) | | | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ | ✓ |
| Thermometer (dual input T1, T2, T1 - T2) | | | | | ✓ | | | | | |
| Dual Capability | | | | | | | | | | |
| mA measure with 24 V loop power | | ✓ | ✓ | | | ✓ | ✓ | ✓ | ✓ | ✓ |
| Switch test | | ✓ | ✓ | | | ✓ | ✓ | ✓ | ✓ | ✓ |
| HART resistor | | ✓ | ✓ | | | ✓ | ✓ | ✓ | ✓ | ✓ |
| IDOS Universal Measurement Modules | ① | ① | ① | ① | ① | ① | ① | ① | ① | ① |
| Features | | | | | | | | | | |
| Programmable step and ramp output | | | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ | ✓ |
| Hold, scaling, max/min/avg, filter, alarm, tare | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| 25 pressure units, flow scaling, leak test | ✓ | ✓ | ② | ② | ② | ② | ② | ② | ② | ② |
| 1000 point data memory, RS232 | ③ | ③ | ③ | ③ | ✓ | ③ | ③ | ③ | ③ | ③ |
| Applications | | | | | | | | | | |
| Measurement and monitoring | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Indicator, controller and recorder testing | ✓ | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ | ✓ |
| Transmitter maintenance and calibration | ✓ | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ | ✓ |
| Process loop set-up and maintenance | ✓ | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ | ✓ |
| Switch, trip and safety system testing | ✓ | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ | ✓ |

① Optional (please refer to IDOS datasheet) ② When fitted with IDOS pressure module
③ Optional (please refer to accessories IO800E)

Advanced Features

Step, ramp, maximum/minimum/average hold and facilitate troubleshooting and system checks



Temperature Instrumentation and Loop Maintenance

DPI 812 RTD Loop Calibrator

Provides simultaneous RTD output and mA measurement for transmitter/loop maintenance

24V Loop Power Supply



Energizes transmitters and control loops

Automatic Switch Test

Captures open/closed trip values providing a fast and highly accurate "safety system" check

HART Resistor

Can be switched into the loop when required by a HART digital communicator and avoids the inconvenience of carrying a 250 Ω resistor



Temperature Test and Measurement

DPI 811 RTD Calibrator

Measures or simulates RTD sensor and is the ideal tool for checking probes, indicators, recorders and controllers

Automatic Detection of Two-, Three- and Four-Wires

Quickly detects faulty sensors and wiring

Pulsed RTD Transmitter Compatibility

Simulation mode

IDOS™ Flexibility

Intelligent Digital Output Sensor (IDOS)

Universal Pressure Modules are available from 10 in H₂O to 10,000 psi (25 mbar to 700 bar).

Total Flexibility

IDOS modules can be used with any compatible instrument; for example, a DPI 812 RTD loop calibrator can become a fully featured pressure calibrator.

DPI 811/812 Specifications

Plug and Play

Modules are interchangeable between instruments, requiring no set-up or instrument calibration.

Please refer to IDOS Universal Pressure Modules data sheet.

DPI 811 and DPI 812

| Measure and Simulate | Standard | *Accuracy | Range |
|----------------------|---------------|-----------------|---------------------------------------|
| Pt 50 (385) | IEC 751 | 0.9°F (0.5°C) | -328°F to 1562°F (-200°C to 850°C) |
| Pt 100 (385) | IEC 751 | 0.45°F (0.25°C) | -328°F to 1562°F (-200°C to 850°C) |
| Pt 200 (385) | IEC 751 | 1.08°F (0.6°C) | -328°F to 1562°F (-200°C to 850°C) |
| Pt 500 (385) | IEC 751 | 0.72°F (0.4°C) | -328°F to 1562°F (-200°C to 850°C) |
| Pt 1000 (385) | IEC 751 | 0.36°F (0.2°C) | -328°F to 752°F (-200°C to 400°C) |
| D 100 (392) | JIS 1604-1989 | 0.45°F (0.25°C) | -328°F to 1202°F (-200°C to 650°C) |
| Ni 100 | DIN 43760 | 0.36°F (0.2°C) | -76°F to 482°F (-60°C to 250°C) |
| Ni 120 | MINCO 7-120 | 0.36°F (0.2°C) | -112°F to 500°F (-80°C to 260°C) |
| Ohms | | 0 to 4000 | 0.1 to 1.3 Ω |

- *Accuracy includes operation over 50°F to 86°F (10°C to 30°C), one year stability and calibration uncertainty.
- Excitation: 0.2 to 0.5 mA measure 0.05 to 3 mA simulate
- Pulse excitation currents minimum duration 10 ms

DPI 812 Only

| Measure | Accuracy |
|-------------------------|---|
| 0 to 55,000 mA | 0.02% reading + 3 counts |
| Temperature coefficient | 14°F to 50°F, 86°F to 122°F, 0.0011% FS/°F (30°C to 50°C, -10°C to 10°C, 0.002% FS °C) |
| Switch detection | Open and closed. 2 mA current |
| Loop power output | 24V ±10% (35 mA maximum) |
| HART mA loop resistor | 250 Ω (menu selection) |
| Electrical connectors | 4 mm sockets |

DPI 800 Series Common Specification

Operating Temperature

14°F to 122°F (-10°C to 50°C)

Storage Temperature

-4°F to 158°F (-20°C to 70°C)

Humidity

0% to 90% non-condensing, Def Stan 66-31, 8.6 Cat III

Shock and Vibration

BS EN61010:2001, Def Stan 66-31, 8.4 Cat III

EMC

BS EN61326-1:1998 + A2:2001

Safety

Electrical BS EN61010:2001, CE marked

Display

Graphic LCD with backlight. Resolution 99999

Size and Weight

7.1 in x 3.3 in x 2 in (180 mm x 85 mm x 50 mm),
14 oz (400 g)

Batteries

3 AA alkaline, >70 hours measure, >10 hours 24 mA source (24V @ 12 mA)

Accessories

IO800A

Soft fabric carrying case with accessory pocket

IO800B

Belt clip, wrist strap/hanging loop and bench stand

IO800C

NiMH batteries with charger, batteries charged externally

IO800E

Data logging upgrade and RS232 lead

DPI 811/812 Specifications

Log data periodically (1 second to 23 hours 59 minutes 59 seconds) or manually by key press. **Review data** on-screen or upload to a PC via the RS232 interface. No software purchase is necessary as standard Microsoft® applications provide data transfer (HyperTerminal) and analysis (Excel). Alternatively, print directly to a compatible serial printer. **Real time clock** with date. **Memory:** 1000 single or 750 dual reading screens with date and time. **Header tag:** 6 user characters to identify groups of readings. **RS232:** 19.2 k baud, 8 data bits, 1 stop bit, no parity, Xon/Xoff. **Data output:** comma separated ASCII.

Ordering Information

Please state the model number DPI 811 or DPI 812 and accessories as separate items.

Supporting Services (order as separate items)

Each unit is supplied with batteries, calibration certificate, user guide and a set of electrical test leads.

Related Products

GE is a world leader in the design and manufacture of pressure, temperature and electrical field calibrators, laboratory/workshop calibration equipment and pressure sensors.

Supporting Services

Our highly trained staff can support you, no matter where you are in the world. We can provide training, nationally accredited calibration - both initially and at periodic intervals - extended warranty terms, maintenance and even rental of portable or laboratory calibrators. Further details can be found in www.gesensing.com/productservices/service.htm



©2008 GE. All rights reserved.
920-111C

All specifications are subject to change for product improvement without notice. GE® is a registered trademark of General Electric Co. Other company or product names mentioned in this document may be trademarks or registered trademarks of their respective companies, which are not affiliated with GE.

www.gesensing.com